



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY  
AND POLLUTION PREVENTION

November 10, 2014

Kevin Kutcel  
Agent for New Nautical Coatings, Inc.  
K RK Consulting LLC  
5807 Churchill Way  
Medina, OH 44256

Subject: Label Notification per PRN 98-10 – Minor label amendments  
Product Name: Sea Hawk Sharkskin Antifouling Paint  
EPA Registration Number: 44891-11  
Application Date: October 7, 2014  
Decision Number: 496361

Dear Mr. Kutcel:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped "Notification" and will be placed in our records.

If you have any questions, you may contact Jose Gayoso at (703) 347-8652 or via email at [gayoso.jose@epa.gov](mailto:gayoso.jose@epa.gov).

Sincerely,



Seiichi Murasaki, Acting Product Manager 33  
Regulatory Management Branch I  
Antimicrobials Division (7510P)  
Office of Pesticide Programs

# Sea Hawk



# Yacht Finishes

## PREMIUM QUALITY

# SHARKSKIN

# Antifouling Paint

**ACTIVE INGREDIENT:**  
Cuprous Oxide..... 45.20%  
**OTHER INGREDIENTS:** 54.80%  
**TOTAL** ..... 100.00%  
Copper expressed as metallic 42.21%  
**CONTAINS PETROLEUM  
DISTILLATES**

**NOTIFICATION**  
Date Reviewed: 11/16/14  
Reviewed By: S-G

**KEEP OUT OF REACH  
OF CHILDREN  
WARNING**

**SEE BACK PANEL FOR ADDITIONAL  
PRECAUTIONARY STATEMENTS**

**LIMITED WARRANTY:** The manufacturer warrants all material sold by it against defects in the material. The manufacturer's liability under the sale and warranty of this material shall in any case be limited to replacement of material only. The manufacturer makes no other warranty of this product, expressed or implied.

**Net Contents  
1 Gallon  
U.S. Measure  
3.785 Liters**



**NEW NAUTICAL COATINGS, INC.**  
14805 49th Street North  
Clearwater, FL 33762  
**[www.seahawkpaints.com](http://www.seahawkpaints.com)**

**DIRECTIONS FOR USE**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

**GENERAL DESCRIPTION**

Traditional, hard, modified epoxy antifoulant that controls the attachment of barnacles, algae, seagrass, green weed and other fouling organisms in fresh and salt water. This product is only for use on the surfaces of hulls on boats, vessels, barges, crab pots and lobster pots.

**SHAKE VIGOROUSLY FOR A MINIMUM OF 10 MINUTES BEFORE APPLICATION**

**PRODUCT INFORMATION**

Finish/Sheen: Semi-Gloss  
 Converter: One Pack  
 Copper Content: 45%  
 Volume Solids: 62%  $\pm$  2%  
 Mix Ratio: One Pack  
 Shipping Weight: 22-24 Lbs./Gal.  
 Flash Point: 80°F/27°C  
 Film Thickness: 5 mils wet equals 3.1 dry per coat  
 Recommended Coats: 2 on entire hull and 3 at waterline  
 Theoretical Coverage: 320 Sq. Ft./Gal. @ recommended film thickness

**APPLICATION DETAILS**

Sweat-In Time: Not applicable  
 Thinner: 2033-2035  
 Cleaner: Sea Hawk Xylene 7130

**Overcoating Interval Drying Time (Hrs)**

Substrate Temp.	Touch	Min.	Max.	Launch
73°F (23°C)	1 Hrs	1 Hr	N/A	12 Hrs
95°F (35°C)	1 Hr	1 Hr	N/A	12 Hrs

**REGULATORY DATA**

**VOC:** 330 Grams/Liter

**LIMITATIONS:** Apply in good weather when air and surface temperature are above 50°F (10°C). Surface temperature must be at least 50°F (10°C) above dew point. For optimum application properties, bring material to 70-80°F (21-27°C) temperature range prior to mixing and application. Unmixed material (in closed containers) should be maintained in protected storage between 40 and 100°F (4-38°C). Prolonged atmospheric exposure of this product may detract from performance. Technical and application data herein is for the purpose of establishing a general guideline for the coating and the proper coating application procedures. As application, environmental and design factors can vary significantly, due care should be exercised in the selection, verification of performance and use of the coating.

**SURFACE PREPARATION:** Paint only clean, dry surfaces. Remove all grease, oil, wax, or other foreign material by solvent or detergent washing. (SSPC-SPI)

**New Construction:** As yard procedures may vary, consult with your Sea Hawk Representative.

**APPLICATION:** Apply by brush, roller or spray. Apply 5 mils wet, which will yield 3.1 mils dry per coat.

**EQUIPMENT**

**Brush:** China Bristle

**Roller:** Solvent resistant roller cover 3/8" pile smooth to medium. Prewash roller cover to remove loose fibers prior to use.

**Airless Spray:** Minimum 28:1 ratio pump; "0.021-0.026" (533-660 microns) orifice tip; 3/8" ID high-pressure material hose; 90 PSI line pressure; 60 mesh filter.

**THINNING:** We do not recommend thinning. However, if thinning is necessary, thin up to a maximum of 10%, with Sea Hawk 2033-2035 only.

**CLEANUP:** Clean all equipment immediately after use with Xylene. It is good practice to

periodically flush out spray equipment during the course of the day. Frequency depends upon the amount sprayed, temperature, elapsed time including delay, etc.

**SAFETY:** Read and observe all precautionary statements on this label.

**STORAGE AND DISPOSAL**

Do not contaminate food, feed or water by storage or disposal.

**Storage:** Do not store near heat or open flame. Store in well ventilated area.

**Pesticide Disposal:** Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**Container Disposal:** Non-refillable container, do not reuse or refill this container. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

**PRECAUTIONARY STATEMENTS****HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**WARNING.** May be fatal if swallowed or inhaled. Causes moderate skin and eye irritation. Harmful if absorbed through skin. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Do not breathe vapors, spray mist, or dust or chips from sanding. Avoid contact with skin, eyes and clothing. While spraying paint or sanding boat surface, wear a mask or pesticide respirator jointly approved by the Mine Safety and Health Administration and the National Institute for Occupational Safety and Health. Wear protective clothing (long-sleeved cotton shirt, long pants and hat) and gloves (such as nitrile or butyl). Wash thoroughly with soap and water after handling and before eating, drinking or using tobacco. Remove contaminated clothing and wash before reuse. Use with adequate ventilation.

**ENVIRONMENTAL HAZARDS**

This pesticide is toxic to fish. Do not apply directly to water by cleaning of equipment or disposing of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

**PHYSICAL AND CHEMICAL HAZARDS**

Combustible. Do not use or store near heat or open flame.

**FIRST AID**

<b>IF SWALLOWED:</b>	• Immediately call a poison control center or doctor • Do not induce vomiting unless told to do so by a poison control center or doctor. • Do not give any liquid to the person. • Do not give anything by mouth to an unconscious person.
<b>IF INHALED:</b>	• Move person to fresh air. • If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. • Call a poison control center or doctor for further treatment advice.
<b>IF IN EYES:</b>	• Hold eye open and rinse slowly and gently with water for 15-20 minutes. • Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. • Call a poison control center or doctor for treatment advice.
<b>IF ON SKIN OR CLOTHING:</b>	• Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15 - 20 minutes. • Call a poison control center or doctor for treatment advice.
For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night. Within USA and Canada 1-800-424-9300. Outside USA and Canada +1-703-527-3887 CHEMTREC. Account #15570.	
For Non Emergencies call New Nautical Coatings Inc., Within the USA and Canada 1-800-528-0997, Outside USA and Canada +1-727-523-8053.	
<b>NOTE TO PHYSICIAN:</b> Contains petroleum distillate, vomiting may cause aspiration pneumonia.	

E.P.A. Reg. No. 44891-11 / E.P.A. Est. No. 44891-FL-1